

CONTOUR™ T24 Installation Instructions

! WARNING

PLEASE READ ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION

- To prevent personal injury or product damage only licensed electricians should install.
- To avoid electric shock or component damage disconnect main power source before attempting installation or servicing.
- This product must be installed in accordance with the national electric code (NEC) and all applicable federal, state and local electric codes and safety standards.
- Disconnect product and allow cooling prior to servicing.
- Any alteration or modification of this product is expressly forbidden as it may cause serious personal injury, death, property damage and/or product malfunction.
- To prevent product malfunction and/or electrical shock this product must be properly grounded.
- Suitable for damp location. Access above required.
- Designed for use in AC110-277V/110-347V,50/60Hz,protected circuit.

UNPACKING

- Unpack and carefully examine the product.
- Report any damage and save all packing material if any part(s) were damaged during shipping.
- 3 Do not attempt to use this apparatus if it is damaged.

INCLUDED IN THE BOX

- LED Luminaire
- 2 Installation Instructions

INSTALLATION INSTRUCTIONS

Step 1

Bend J-Hook by 45° making it vertical to the rear cover of LED luminaire (Figure 1A). Bend the top part of J-Hook by 90° (Figure 1B). Repeat STEP1 to other J-Hooks.





Figure 1A

Figure 1B




Turn off power, remove the ceiling panel, then place LED luminaire into the T-bar, ensure the LEDI uminaire is attached to the ceiling.(Figure 2) (J-Hook for positioning only)




Step 3

Open the driver box.(Figure 3) (trade size of conduit: 22.2mm dia)




Step 4

- Connect AC Wires
 Input L connect to the black wire of the luminaire, N connects to the white wire, the Ground connects to the green wire.
- Connect Dimmer
 Compatible with 0-10V dimmer
 The Driver Connects to the Violet (D+) to the dimmer (+) and driver the Pink (D-)
 Connect to the dimmer (-./



Step 5

Close the drier box and screw in (Figure 5)



WIRING DIAGRAM

