

Changing the World, One Bulb at a Time.



TRUEFIT™ LED TUBE



Features & Benefits:


- Ballast-Compatible LED T8/T12 Fluorescent Replacement
- High-Efficiency Solid State LED Array
- 50%+ Savings in Energy Consumption
- Advanced Heat Sink and Optical Diffuser
- 50,000 Hour Warranty
- Shock and Vibration Resistant
- Mercury Free
- 120~277V Compatible
- UL And DLC Listed
- Includes Backup Power Supply
Never Replace a Ballast Again

Applications:


- | | |
|---------------|-----------------------|
| Offices | Buses |
| Classrooms | Trains |
| Lobbies | Warehouses |
| Back-of-house | Parking Lots |
| Restaurants | Retail Displays |
| Malls | Backlighting: |
| Hotels | -Square Billboards |
| | -Advertisement Boards |



1. Turn Off



2. Remove
Fluorescent Tube



3. Install
TrueFit™ Tube



4. Turn On



Due to advancements in technology, specifications are subject to change without notice.

All images are copyright Truly Green Solutions, Inc. and may be only be used with permission.

WARNING: READ INSTRUCTIONS BEFORE INSTALLING

Disconnect all power sources to the fixtures before installing.

www.trulygreensolutions.com | info@trulygreensolutions.com P: 818.206.4404 | F: 866.577.5302



TRUEFIT™ LED TUBE



15W



18W

Product Model	834015 / 834115	834018 / 834118
Comparable To Fluorescent	32~40W	32~54W
Technical Parameters	15W	18W
Input Voltage	120~277VAC	120~277VAC
Power Frequency	50~60Hz	50~60Hz
Total Power Consumption	15W	18W
LED Power Consumption	15W	18W
LED Chip	96pcs	120pcs
Power Factor	>0.90	>0.90
Luminous Flux(IES)	1700 lm	2070 lm
CRI	≥80	≥80
Colour Temperature	3000~5000K	3000~5000K
Beam Angle	180°	180°
IP Rating	N/A	N/A
Operating Temperature	-35°C~50°C	-35°C~50°C
Lumen Maintenance	50,000Hrs	50,000Hrs
Light Fixture Material	Aluminum Profile & PC Cover	Aluminum Profile & PC Cover
Dimensions (D×L)	26x1200mm	26x1200mm
Sockets Base	2 Pin (G13)	2 Pin (G13)
PC Cover	Clear or Frosted	Clear or Frosted
Dimmable	No	No



Due to advancements in technology, specifications are subject to change without notice.

All images are copyright Truly Green Solutions, Inc. and may be only be used with permission.

WARNING: READ INSTRUCTIONS BEFORE INSTALLING

Disconnect all power sources to the fixtures before installing.



Cost Effective

The best choice in reducing the effects of surging power costs across over world.
Saves up to 66.5% of power compared to Fluorescent.

Power Consumption	Lumens	Comparable To Fluorescent	Energy Saving
15W	1700 lm	32~40W	63%
18W	2070 lm	32~54W	67%

TrueFit™ LED Tube Light Replaces Fluorescent

LED

Fluorescent



TrueFit™
15W 4ft

Fluorescent
32~40W



TrueFit™
18W 4ft

Fluorescent
32~54W



Due to advancements in technology, specifications are subject to change without notice.

All images are copyright Truly Green Solutions, Inc. and may be only be used with permission.

WARNING READ INSTRUCTIONS BEFORE INSTALLING

Disconnect all power sources to the fixtures before installing.

www.trulygreensolutions.com | info@trulygreensolutions.com P: 818.206.4404 | F: 866.577.5302



Ordering Information – TrueFit™ 15W 4'

834015-50-B-C TrueFit™ Ballast Compatible 15W LED Tube (5000K) Clear

834115-50-B-F TrueFit™ Ballast Compatible 15W LED Tube (5000K) Frosted

834015-40-B-C TrueFit™ Ballast Compatible 15W LED Tube (4000K) Clear

834115-40-B-F TrueFit™ Ballast Compatible 15W LED Tube (4000K) Frosted

834015-35-B-C TrueFit™ Ballast Compatible 15W LED Tube (3500K) Clear

834115-35-B-F TrueFit™ Ballast Compatible 15W LED Tube (3500K) Frosted

Ordering Information – TrueFit™ 18W 4'

834018-50-B-C TrueFit™ Ballast Compatible 18W LED Tube (5000K) Clear

834118-50-B-F TrueFit™ Ballast Compatible 18W LED Tube (5000K) Frosted

834018-40-B-C TrueFit™ Ballast Compatible 18W LED Tube (4000K) Clear

834118-40-B-F TrueFit™ Ballast Compatible 18W LED Tube (4000K) Frosted

834018-35-B-C TrueFit™ Ballast Compatible 18W LED Tube (3500K) Clear

834118-35-B-F TrueFit™ Ballast Compatible 18W LED Tube (3500K) Frosted

Due to advancements in technology, specifications are subject to change without notice.

All images are copyright Truly Green Solutions, Inc. and may be only be used with permission.

WARNING: READ INSTRUCTIONS BEFORE INSTALLING

Disconnect all power sources to the fixtures before installing.

www.trulygreensolutions.com | info@trulygreensolutions.com P: 818.206.4404 | F: 866.577.5302