Not all products are qualified on the DLC® QPL. To view our DLC® qualified products, please consult the DLC® Qualified Products List at www.designlights.org/qpl.

TRUET5™ EXT (DIMMABLE)

www.trulygreensolutions.com

TRULY GREEN SOLUTIONS

Features

Not all products are qualified on the DLC® QPL. To view our DLC® qualified products, please consult the DLC® Qualified Products List at www.design-lights.org/qpl.

5 YEAR WARRANTY

3 LENGTHS AVAILABLE IN 15W/18W/22W/25W/30W

EXPECTED LIFE OVER 50,000 HRS

IES FILES @ www.trulygreensolutions.com

SUITABLE FOR DAMP LOCATIONS

GLARE FREE PC LENS



SELECTION OF COLOR RANGES

Type A : Ballast Compatible
Type B : Bypass Ballast
Type A/B : Ballast Compatible or Bypass Ballast
Type C : External Power

EASY INSTALLATION



Applications

Parking Garage

Mall

Storage Facility

Specifications and dimensions subject to change without notice.
All images are copyright Truly Green Solutions, LLC and may be only be used with permission.
www.trulygreensolutions.com I Tel: 818-206-4404 I Fax: 866-577-5302 I info@trulygreensolutions.com

4' 22W
SPECIFICATIONS

5 YEAR WARRANTY

Replaces 4'T5 Fluorescent Tubes

Highlights

The TGS TrueT5™ EXT LED T5 lamp offers an easy and safe energy-saving retrofit solution for fluorescent T5 or T5 HO tubes, with up to 130 lumens per watt. The long-lasting and high-quality TrueT5™ is powered by an external driver, allowing bypass of the existing ballast to eliminate compatibility issues and maintenance costs associated with ballasts.

The TrueT5™ LED T5 lamp provides superior quality uniform, flicker-free lighting in a compact package. It uses about half the energy as fluorescent T5 tubes, with up to 70% reduction of overall operating costs. The UL, cUL, and RoHS certified lamps are available in 2', 3' and 4' lengths, in 4 different wattages (15W, 18W, 22W, 25W, and 30W), with the form, fit and function of traditional T5 fluorescent lamps. The TrueT5™ is constructed with a polycarbonate optical diffuser, which provides a wide beam angle of 120° for comprehensive spatial illumination.

Featuring a unique advanced heat sink technology that ensures maximum thermal management, the TrueT5™ EXT is backed by a 5 year/50,000 hour warranty for a long life of maintenance-free service. Available CCT's are 3000K, 3500K, 4000K and 5000K.

Product Dimensions

Length: 47.24 in (1200mm) [Pin to Pin]
Length: 45.20 in (1148mm) [Cap to Cap]
Weight: 0.419 lbs (190g)
Diameter: 0.8 in (21mm)



Optical Details

System Efficacy	130 LpW
Lumen Output	2,860 lm
CCT	3000K, 3500K, 4000K, 5000K
Beam Angle	120°
CRI	>80
System Efficiency	N/A

Electrical Details

Input Voltage	100-277V AC (347V Available)
Power Frequency	50-60 Hz
Output Voltage	N/A
Output Current	N/A
Power Efficiency	99%
Power Factor	>0.99
Total Harmonic Distortion	<20%
Dimmable	Yes

Other Details

System Power Usage	22W
LED Power Usage	N/A
Fixture Material	Aluminum Base and PC Cover
Finish	N/A
Ingress Protection	Suitable For Damp Locations
Luminaire Net Weight	0.419 lbs (190g)
Lifespan	50,000+ Hours
Storage Temperature	-4°~122°F
Operating Temperature	-4°~104°F
Operating Humidity	N/A
Product Dimension	47.24x0.8 in (pin to pin)
Replaces (HID, CFL, MH, HPS, Fluor)	T5 Fluorescent

Application

• Offices	• Hospitals
• Industrial Shops	• Hotels
• Schools	• High / Low Bay
• Commercial Buildings	• Troffers / Strips

Pin Type

• G5 Pin (Bipin)

Specifications and dimensions subject to change without notice.
All images are copyright Truly Green Solutions, LLC and may be only be used with permission.
www.trulygreensolutions.com I Tel: 818-206-4404 I Fax: 866-577-5302 I info@trulygreensolutions.com

Driver Dimensions

Input

Wire Color	Assignment
Red	AC L
Black	AC N

Output

Wire Color	Assignment
Red	LED 1 +
Black	LED 1 -
Blue	Dim -
Brown	Dim +





Rated Power: 15W
Frequency: 50-60Hz
Voltage Range:100-277V AC

Rated Current: 380mA
DC Voltage: 40V
Constant Current Region: 30-40V





Rated Power: 18W and 22W
Frequency: 50-60Hz
Voltage Range:100-277V AC

Rated Current: 540mA
DC Voltage: 40V
Constant Current Region: 30-40V



Rated Power: 30W
Frequency: 50-60Hz
Voltage Range:100-277V AC

Rated Current: 700mA
DC Voltage: 40V
Constant Current Region: 30-40V

Specifications and dimensions subject to change without notice.
All images are copyright Truly Green Solutions, LLC and may be only be used with permission.
www.trulygreensolutions.com I Tel: 818-206-4404 I Fax: 866-577-5302 I info@trulygreensolutions.com

Driver Dimensions

Input

Wire Color	Assignment
Red	AC L
Black	AC N

Output

Wire Color	Assignment
Red	LED 1 +
Black	LED 1 -
Brown	Dim +
Yellow	Dim –





Rated Power: 40W
Frequency: 50-60Hz
Voltage Range:100-277V AC

Rated Current: 1000mA
DC Voltage: 40V





Rated Power: 50W
Frequency: 50-60Hz
Voltage Range:100-277V AC

Rated Current: 1500mA
DC Voltage: 28-40V





Rated Power: 60W
Frequency: 50-60Hz
Voltage Range:100-277V AC

Rated Current: 1680mA
DC Voltage: 28-40V

Specifications and dimensions subject to change without notice.
All images are copyright Truly Green Solutions, LLC and may be only be used with permission.
www.trulygreensolutions.com I Tel: 818-206-4404 I Fax: 866-577-5302 I info@trulygreensolutions.com

Lumen Packages

1 Tube/1 Driver:	Driver:
15W = 1,950 lm	15W
18W = 2,340 lm	22W
22W = 2,860 lm	22W
25W = 3,250 lm	25W
30W = 3,600 lm	30W

3 Tube/1 Driver:	Driver:
15W = 5,850 lm	40W
18W = 7,020 lm	60W
22W = 8,580 lm	50W

2 Tube/1 Driver:	Driver:
15W = 3,900 lm	30W
18W = 4,680 lm	40W
22W = 5,720 lm	40W
25W = 6,500 lm	50W
30W = 7,200 lm	50W

4 Tube/1 Driver:	Driver:
15W = 7,800 lm	50W

*4 Tube/2 Driver
Also Available

*** Note:**

- **2' and 3' only available in 15W**
- **15', 18W, 22W, 25W, and 30W available in 4'**

Specifications and dimensions subject to change without notice.
All images are copyright Truly Green Solutions, LLC and may be only be used with permission.
www.trulygreensolutions.com I Tel: 818-206-4404 I Fax: 866-577-5302 I info@trulygreensolutions.com

Ordering Information

EXAMPLE NUMBER: 832115-40-T5-F-A-D-D

83	Length	Wattage	CCT	Tube Type	Lens Cover	Tube Quantity	D	Dimmable
TrueT5™ EXT	21 - 24"	15 - 15W	50 - 5000K 40 - 4000K 35 - 3500K 30 - 3000K	T5	F - Frosted	A - One Tube One Driver B - Two Tube One Driver C - Three Tube One Driver D - Four Tube One Driver	D	D - Dimmable

EXAMPLE NUMBER: 833115-40-T5-F-A-D-D

83	Length	Wattage	CCT	Tube Type	Lens Cover	Tube Quantity	D	Dimmable
TrueT5™ EXT	31 - 36"	15 - 15W	50 - 5000K 40 - 4000K 35 - 3500K 30 - 3000K	T5	F - Frosted	A - One Tube One Driver B - Two Tube One Driver C - Three Tube One Driver D - Four Tube One Driver	D	D - Dimmable

EXAMPLE NUMBER: 834115-40-T5-F-A-D-D

83	Length	Wattage	CCT	Tube Type	Lens Cover	Tube Quantity	D	Dimmable
TrueT5™ EXT	41 - 48"	15 - 15W 18 - 18W 22 - 22W 25 - 25W 30 - 30W	50 - 5000K 40 - 4000K 35 - 3500K 30 - 3000K	T5	F - Frosted	A - One Tube One Driver B - Two Tube One Driver C - Three Tube One Driver D - Four Tube One Driver	D	D - Dimmable

*** Note:**

- **2' and 3' only available in 15W**
- **15', 18W, 22W, and 30W available in 4'**

Emergency Battery Backup Accessory Options

EXAMPLE NUMBER: 90012-L

900	Wattage	High Voltage
High Voltage LED Emergency Battery Backup	8 - 8W 12 -12W 25 - 25W	L

Accessory: Tombstone

EXAMPLE NUMBER: 9913-B-T5

	Tombstone
Tomb-stones	9913-B-T5 (Shunted Tombstone Socket - Double-End Power)

Specifications and dimensions subject to change without notice.
All images are copyright Truly Green Solutions, LLC and may be only be used with permission.
www.trulygreensolutions.com I Tel: 818-206-4404 I Fax: 866-577-5302 I info@trulygreensolutions.com

One Tube and One Driver SKU Numbers:

SKU Number	Base Type	Wattage	Color Temp (K)	Dimensions	Lumens (lm)	Input Voltage	Warranty	DLC® Qualified
832115-50-T5-F-A-D-D	G5	15W	5000	23.62"x0.8"	1,950	100-277V	5 year	No
832115-40-T5-F-A-D-D	G5	15W	4000	23.62"x0.8"	1,950	100-277V	5 year	No
832115-35-T5-F-A-D-D	G5	15W	3500	23.62"x0.8"	1,950	100-277V	5 year	No
832115-30-T5-F-A-D-D	G5	15W	3000	23.62"x0.8"	1,950	100-277V	5 year	No
833115-50-T5-F-A-D-D	G5	15W	5000	35.43"x0.8"	1,950	100-277V	5 year	No
833115-40-T5-F-A-D-D	G5	15W	4000	35.43"x0.8"	1,950	100-277V	5 year	No
833115-35-T5-F-A-D-D	G5	15W	3500	35.43"x0.8"	1,950	100-277V	5 year	No
833115-30-T5-F-A-D-D	G5	15W	3000	35.43"x0.8"	1,950	100-277V	5 year	No
834115-50-T5-F-A-D-D	G5	15W	5000	47.24"x0.8"	1,950	100-277V	5 year	No
834115-40-T5-F-A-D-D	G5	15W	4000	47.24"x0.8"	1,950	100-277V	5 year	No
834115-35-T5-F-A-D-D	G5	15W	3500	47.24"x0.8"	1,950	100-277V	5 year	No
834115-30-T5-F-A-D-D	G5	15W	3000	47.24"x0.8"	1,950	100-277V	5 year	No
834118-50-T5-F-A-D-D	G5	18W	5000	47.24"x0.8"	2,340	100-277V	5 year	No
834118-40-T5-F-A-D-D	G5	18W	4000	47.24"x0.8"	2,340	100-277V	5 year	No
834118-35-T5-F-A-D-D	G5	18W	3500	47.24"x0.8"	2,340	100-277V	5 year	No
834118-30-T5-F-A-D-D	G5	18W	3000	47.24"x0.8"	2,340	100-277V	5 year	No
834122-50-T5-F-A-D-D	G5	22W	5000	47.24"x0.8"	2,860	100-277V	5 year	No
834122-40-T5-F-A-D-D	G5	22W	4000	47.24"x0.8"	2,860	100-277V	5 year	No
834122-35-T5-F-A-D-D	G5	22W	3500	47.24"x0.8"	2,860	100-277V	5 year	No
834122-30-T5-F-A-D-D	G5	22W	3000	47.24"x0.8"	2,860	100-277V	5 year	No
834125-50-T5-F-A-D-D	G5	25W	5000	47.24"x0.8"	3,250	100-277V	5 year	No
834125-40-T5-F-A-D-D	G5	25W	4000	47.24"x0.8"	3,250	100-277V	5 year	No
834125-35-T5-F-A-D-D	G5	25W	3500	47.24"x0.8"	3,250	100-277V	5 year	No
834125-30-T5-F-A-D-D	G5	25W	3000	47.24"x0.8"	3,250	100-277V	5 year	No
834130-50-T5-F-A-D-D	G5	30W	5000	47.24"x0.8"	3,600	100-277V	5 year	No
834130-40-T5-F-A-D-D	G5	30W	4000	47.24"x0.8"	3,600	100-277V	5 year	No
834130-35-T5-F-A-D-D	G5	30W	3500	47.24"x0.8"	3,600	100-277V	5 year	No
834130-30-T5-F-A-D-D	G5	30W	3000	47.24"x0.8"	3,600	100-277V	5 year	No

Specifications and dimensions subject to change without notice.
All images are copyright Truly Green Solutions, LLC and may be only be used with permission.
www.trulygreensolutions.com I Tel: 818-206-4404 I Fax: 866-577-5302 I info@trulygreensolutions.com

Two Tube and One Driver SKU Numbers:

SKU Number	Base Type	Wattage	Color Temp (K)	Dimensions	Lumens (lm)	Input Voltage	Warranty	DLC® Qualified
832115-50-T5-F-B-D-D	G5	15W	5000	23.62″x0.8″	3,900	100-277V	5 year	Yes
832115-40-T5-F-B-D-D	G5	15W	4000	23.62″x0.8″	3,900	100-277V	5 year	Yes
832115-35-T5-F-B-D-D	G5	15W	3500	23.62″x0.8″	3,900	100-277V	5 year	Yes
832115-30-T5-F-B-D-D	G5	15W	3000	23.62″x0.8″	3,900	100-277V	5 year	Yes
833115-50-T5-F-B-D-D	G5	15W	5000	35.43″x0.8″	3,900	100-277V	5 year	Yes
833115-40-T5-F-B-D-D	G5	15W	4000	35.43″x0.8″	3,900	100-277V	5 year	Yes
833115-35-T5-F-B-D-D	G5	15W	3500	35.43″x0.8″	3,900	100-277V	5 year	Yes
833115-30-T5-F-B-D-D	G5	15W	3000	35.43″x0.8″	3,900	100-277V	5 year	Yes
834115-50-T5-F-B-D-D	G5	15W	5000	47.24″x0.8″	3,900	100-277V	5 year	Yes
834115-40-T5-F-B-D-D	G5	15W	4000	47.24″x0.8″	3,900	100-277V	5 year	Yes
834115-35-T5-F-B-D-D	G5	15W	3500	47.24″x0.8″	3,900	100-277V	5 year	Yes
834115-30-T5-F-B-D-D	G5	15W	3000	47.24″x0.8″	3,900	100-277V	5 year	Yes
834118-50-T5-F-B-D-D	G5	18W	5000	47.24″x0.8″	4,860	100-277V	5 year	Yes
834118-40-T5-F-B-D-D	G5	18W	4000	47.24″x0.8″	4,860	100-277V	5 year	Yes
834118-35-T5-F-B-D-D	G5	18W	3500	47.24″x0.8″	4,860	100-277V	5 year	Yes
834118-30-T5-F-B-D-D	G5	18W	3000	47.24″x0.8″	4,860	100-277V	5 year	Yes
834122-50-T5-F-B-D-D	G5	22W	5000	47.24″x0.8″	5,720	100-277V	5 year	Yes
834122-40-T5-F-B-D-D	G5	22W	4000	47.24″x0.8″	5,720	100-277V	5 year	Yes
834122-35-T5-F-B-D-D	G5	22W	3500	47.24″x0.8″	5,720	100-277V	5 year	Yes
834122-30-T5-F-B-D-D	G5	22W	3000	47.24″x0.8″	5,720	100-277V	5 year	Yes
834125-50-T5-F-B-D-D	G5	25W	5000	47.24″x0.8″	6,500	100-277V	5 year	Yes
834125-40-T5-F-B-D-D	G5	25W	4000	47.24″x0.8″	6,500	100-277V	5 year	Yes
834125-35-T5-F-B-D-D	G5	25W	3500	47.24″x0.8″	6,500	100-277V	5 year	Yes
834125-30-T5-F-B-D-D	G5	25W	3000	47.24″x0.8″	6,500	100-277V	5 year	Yes
834130-50-T5-F-B-D-D	G5	30W	5000	47.24″x0.8″	7,200	100-277V	5 year	Yes
834130-40-T5-F-B-D-D	G5	30W	4000	47.24″x0.8″	7,200	100-277V	5 year	Yes
834130-35-T5-F-B-D-D	G5	30W	3500	47.24″x0.8″	7,200	100-277V	5 year	Yes
834130-30-T5-F-B-D-D	G5	30W	3000	47.24″x0.8″	7,200	100-277V	5 year	Yes

Not all products are qualified on the DLC® QPL. To view our DLC® qualified products, please consult the DLC® Qualified Products List at www.design-lights.org/qpl.

Specifications and dimensions subject to change without notice.
All images are copyright Truly Green Solutions, LLC and may be only be used with permission.
www.trulygreensolutions.com I Tel: 818-206-4404 I Fax: 866-577-5302 I info@trulygreensolutions.com

Three Tube and One Driver SKU Numbers:

SKU Number	Base Type	Wattage	Color Temp (K)	Dimensions	Lumens (lm)	Input Voltage	Warranty	DLC® Qualified
832115-50-T5-F-C-D-D	G5	15W	5000	23.62"x0.8"	5,850	100-277V	5 year	Yes
832115-40-T5-F-C-D-D	G5	15W	4000	23.62"x0.8"	5,850	100-277V	5 year	Yes
832115-35-T5-F-C-D-D	G5	15W	3500	23.62"x0.8"	5,850	100-277V	5 year	Yes
832115-30-T5-F-C-D-D	G5	15W	3000	23.62"x0.8"	5,850	100-277V	5 year	Yes
833115-50-T5-F-C-D-D	G5	15W	5000	35.43"x0.8"	5,850	100-277V	5 year	Yes
833115-40-T5-F-C-D-D	G5	15W	4000	35.43"x0.8"	5,850	100-277V	5 year	Yes
833115-35-T5-F-C-D-D	G5	15W	3500	35.43"x0.8"	5,850	100-277V	5 year	Yes
833115-30-T5-F-C-D-D	G5	15W	3000	35.43"x0.8"	5,850	100-277V	5 year	Yes
834115-50-T5-F-C-D-D	G5	15W	5000	47.24"x0.8"	5,850	100-277V	5 year	Yes
834115-40-T5-F-C-D-D	G5	15W	4000	47.24"x0.8"	5,850	100-277V	5 year	Yes
834115-35-T5-F-C-D-D	G5	15W	3500	47.24"x0.8"	5,850	100-277V	5 year	Yes
834115-30-T5-F-C-D-D	G5	15W	3000	47.24"x0.8"	5,850	100-277V	5 year	Yes
834118-50-T5-F-C-D-D	G5	18W	5000	47.24"x0.8"	7,020	100-277V	5 year	Yes
834118-40-T5-F-C-D-D	G5	18W	4000	47.24"x0.8"	7,020	100-277V	5 year	Yes
834118-35-T5-F-C-D-D	G5	18W	3500	47.24"x0.8"	7,020	100-277V	5 year	Yes
834118-30-T5-F-C-D-D	G5	18W	3000	47.24"x0.8"	7,020	100-277V	5 year	Yes
834122-50-T5-F-C-D-D	G5	22W	5000	47.24"x0.8"	8,580	100-277V	5 year	Yes
834122-40-T5-F-C-D-D	G5	22W	4000	47.24"x0.8"	8,580	100-277V	5 year	Yes
834122-35-T5-F-C-D-D	G5	22W	3500	47.24"x0.8"	8,580	100-277V	5 year	Yes
834122-30-T5-F-C-D-D	G5	22W	3000	47.24"x0.8"	8,580	100-277V	5 year	Yes

Not all products are qualified on the DLC® QPL. To view our DLC® qualified products, please consult the DLC® Qualified Products List at www.design-lights.org/qpl.

Specifications and dimensions subject to change without notice.
All images are copyright Truly Green Solutions, LLC and may be only be used with permission.
www.trulygreensolutions.com I Tel: 818-206-4404 I Fax: 866-577-5302 I info@trulygreensolutions.com

Four Tube and One Driver SKU Numbers:

SKU Number	Base Type	Wattage	Color Temp (K)	Dimensions	Lumens (lm)	Input Voltage	Warranty	DLC® Qualified
832115-50-T5-F-D-D-D	G5	15W	5000	23.62″x0.8″	7,800	100-277V	5 year	Yes
832115-40-T5-F-D-D-D	G5	15W	4000	23.62″x0.8″	7,800	100-277V	5 year	Yes
832115-35-T5-F-D-D-D	G5	15W	3500	23.62″x0.8″	7,800	100-277V	5 year	Yes
832115-30-T5-F-D-D-D	G5	15W	3000	23.62″x0.8″	7,800	100-277V	5 year	Yes
833115-50-T5-F-D-D-D	G5	15W	5000	35.43″x0.8″	7,800	100-277V	5 year	Yes
833115-40-T5-F-D-D-D	G5	15W	4000	35.43″x0.8″	7,800	100-277V	5 year	Yes
833115-35-T5-F-D-D-D	G5	15W	3500	35.43″x0.8″	7,800	100-277V	5 year	Yes
833115-30-T5-F-D-D-D	G5	15W	3000	35.43″x0.8″	7,800	100-277V	5 year	Yes
834115-50-T5-F-D-D-D	G5	15W	5000	47.24″x0.8″	7,800	100-277V	5 year	Yes
834115-40-T5-F-D-D-D	G5	15W	4000	47.24″x0.8″	7,800	100-277V	5 year	Yes
834115-35-T5-F-D-D-D	G5	15W	3500	47.24″x0.8″	7,800	100-277V	5 year	Yes
834115-30-T5-F-D-D-D	G5	15W	3000	47.24″x0.8″	7,800	100-277V	5 year	Yes

Not all products are qualified on the DLC® QPL. To view our DLC® qualified products, please consult the DLC® Qualified Products List at www.design-lights.org/qpl.

Specifications and dimensions subject to change without notice.
All images are copyright Truly Green Solutions, LLC and may be only be used with permission.
www.trulygreensolutions.com I Tel: 818-206-4404 I Fax: 866-577-5302 I info@trulygreensolutions.com