INDOOR

tgs

Date:	
Project Name:	
Sku #:	

Contemporary Vanity III

Wall Mounted

5CCT
Field Selectable

MOUNTING OPTIONS

Flush Mount
(Standard)

APPLICATIONS

Bathroom, Bedroom, Dressing Room, Etc

FEATURES

Construction

- Die-formed Cold-rolled Steel
- Powder Coated Paint

Finish

- Brushed Nickel
- Black*
- White*

Electrical & Technical

- Input Voltage: 120V
- Input Frequency: 60Hz
- Projected L70 > 50,000 hrs
- PF: >0.95
- CRI: >80 or >90* [Option]
- THD: <20%
- CCT Selectable: 2700K/ 3000K/ 3500K/4000K/5000K
- Operating Temp.: -4°F~113°F
- Damp Location Rated

Optical

- High Transmission White Acrylic Lens
- 270° Beam Angle

Installation/Mounting

- Wall Mounted

Controls

- Triac Dimming

Compliance

- JA8 TITLE 24 Compliant at 90CRI

Dimmer Compatibility List:

Leviton: IPL06-10Z, 6672-1LW, 6674-P0W, DLS06-1LZ
Lutron: TGCL-153P, MACL-153M, CTCL-153P, PD-6WCL

Lumen Output

- 18"/20W: 1,600lm
- 24"/25W: 2,000lm
- 36"/30W: 2,400lm
- 48"/35W: 2,800lm

Warranty

- 5 Year Warranty

See warranty documentation for more information.

80+ CRI · Damp Location · Intertek · ENERGY STAR · FC · CALIFORNIA JA8 TITLE 24 COMPLIANT LAMP

ORDERING INFORMATION

EXAMPLE: VF3-2425-CC-BN

VF3				
Series	**Size/Wattage**	**CCT**	**Finish**	**CRI Option**
VF3	1820 - 18"/20W 2425 - 24"/25W 3630 - 36"/30W 4835 - 48"/35W	CC - 2700K/3000K/3500K/4000K/5000K	BN - Brushed Nickel BK - Black* WH - White*	90CRI (Option*)

Contemporary Vanity III

Wall Mounted

DIMENSIONS





LUMEN OUTPUT

SKU	Size (in)	Wattage (W)	Delivered Lumens (lm)	Efficacy (lm/W)
VF3-1820-CC-BN	18	20	1600	80
VF3-2425-CC-BN	24	25	2000	80
VF3-3630-CC-BN	36	30	2400	80
VF3-4835-CC-BN	48	35	2800	80

9601 Variel Ave, Chatsworth, CA 91311
(818) - 206 - 4404

Specifications & dimensions subject to change without notice.
*MOQ & longer lead times may apply, please contact customer service for more information.