


Date:	
Project Name:	
SKU #:	

ICON R6™
Icon Series Round Downlight 6"



TRIM FINISH

See Page 3 for All Available Trim Types




White Trim Black Trim

APPLICATIONS

Residential, Commercial, Multi-Family

FEATURES

- | | |
|--|---|
| <p>Construction</p> <ul style="list-style-type: none"> - Aluminum Housing <p>Electrical & Technical</p> <ul style="list-style-type: none"> - Input Voltage: 120-277VAC - Input Frequency: 60Hz - Projected Life: L70 > 50,000 hrs - PF: >0.9 - CRI: >90 - THD: <20% - CCT Selectable: 2700K/3000K/3500K/4000K/5000K - Dim to Warm [3000K-1800K] [Option] - Operating Temp.: -4°F ~ 104°F - Wet Location Rated - IC Rated - 25 W Emergency Battery Backup [Option] <p>Controls</p> <ul style="list-style-type: none"> - Dual Mode: 0-10V Dimming [120-277V] + Triac Dimming [120V] - Triac Dimming [120V for Dim to Warm] <p>Dimmer Compatibility List:</p> <ul style="list-style-type: none"> - See Page 3 <p>Lumen Output</p> <ul style="list-style-type: none"> • See Page 2 | <p>Finish</p> <ul style="list-style-type: none"> - White Trim - Black Trim [Option] <p>Optical</p> <ul style="list-style-type: none"> - White PC Lens - Beam Angles: 24° Narrow 38° Medium 60° Wide <p>Installation/Mounting</p> <ul style="list-style-type: none"> - Spring Clip Mount [W/Trim]: Ceiling Cutout: Ø5.71" <p>Compliance</p> <ul style="list-style-type: none"> - JA8 TITLE 24 Compliant <p>Warranty</p> <ul style="list-style-type: none"> - 5 Year Warranty See warranty documentation for more information. |
|--|---|




ORDERING INFORMATION **EXAMPLE: ICON-R-6-24-5C-38-RTM-WH**

Series	Size	Wattage	CCT	Input Voltage	Beam Angle	Trim Type	Trim Finish
ICON-R	6 - 6"	24 - 24W	5C - 2700K/3000K/3500K/4000K/5000K	U - 120-277VAC	24 - 24° 38 - 38° 60 - 60°	RTM - Round Trim	BK - Black WH - White
			DW - Dim to Warm (3000K-1800K)	T - 120VAC			

Accessories

- ICON-SR-6-CP [Construction Plate Kit]
- FLEX-6 [6' Flexible Connector]
- FLEX-10 [10' Flexible Connector]
- FLEX-20 [20' Flexible Connector]
- EM [25W Emergency Battery Backup]

DIMENSIONS



LUMEN OUTPUT

SKU	Size (in)	Wattage (W)	Beam Angle	2700K		3000K		3500K		4000K		5000K	
				Delivered Lumens (lm)	Efficacy (lm/W)	Delivered Lumens (lm)	Efficacy (lm/W)	Delivered Lumens (lm)	Efficacy (lm/W)	Delivered Lumens (lm)	Efficacy (lm/W)	Delivered Lumens (lm)	Efficacy (lm/W)
ICON-R-6-24-5C-24-RTM-WH	6	24	24°	1664	78	1794	75	1977	95	2082	90	2116	99
ICON-R-6-24-5C-38-RTM-WH	6	24	38°	1614	70	1717	75	1949	87	2027	90	2036	89
ICON-R-6-24-5C-60-RTM-WH	6	24	60°	1732	81	1857	88	2043	99	2149	103	2281	103

ACCESSORIES



Round Trim
[RTM]



Construction Plate Kit
[ICON-SR-6-CP]



25W
Emergency Battery Backup
[Factory Install]
[EM]



6'/10'/20'
Flexible Extension Connector
[FLEX-6]
[FLEX-10]
[FLEX-20]

COMPLETED PRODUCT



ICON R6™
Round Trim

DIMMER COMPATABILITY LIST

TRIAC Dimming:

Leviton: 6672, 6674, IPL06

Lutron: LECL-153P, CTCL-150H, LGCL-153PLH, CTCL-153P, SCL-153P, S-600P, PD-6WCL, PD-5NE, PD-10NXD, DVCL-153P, TGCL-153P, AYCL-153P, MACL-153M

Eaton: AAL06

Pass & Seymour: DCL453PTCCCV6

GE: 10464, 18027

0-10V Dimming:

Leviton: Illumitech - IP7

Lutron: Diva - DVTV, Diva - NFTV, Nova T - NTFTV

Watt Stopper: DCLV1

Lightolier Controls: ZP600FAM120

Philips: Sunrise - SR1200ZTUNV