Vista™ Two Light Vanity
Installation Instructions

⚠ WARNING

PLEASE READ ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION

— To prevent personal injury or product damage only licensed electricians should install.
— To avoid electric shock or component damage disconnect power before attempting installation or servicing.
— This product must be installed in accordance with the National Electrical Code (NEC) and all applicable federal, state and local electrical codes and safety standards.
— Disconnect product and allow cooling prior to servicing.
— Any alteration or modification of this product is expressly forbidden as it may cause serious personal injury, death, property damage and/or product malfunction.
— To prevent product malfunction and/or electrical shock this product must be properly grounded.
— This product must be installed in accordance with the applicable installation code by a Person familiar with the construction and operation of the product and the hazards involved.

Step 1: Disconnect Power

Turn OFF power at the circuit breaker. Verify that the electrical supply is de-energized before proceeding.

Step 2: Install Mounting Bracket

Position the mounting bracket (1) over the ceiling junction box. Secure the bracket using the mounting screws (2). Ensure the bracket is properly aligned and securely fastened.

Step 3: Connect Electrical Wiring

Support the fixture while making electrical connections. Using the provided wire connectors (3), connect the fixture conductors to the corresponding supply conductors:

Black (Line/Hot): Connect to the supply line conductor.
White (Neutral): Connect to the supply neutral conductor.
Green/Bare (Ground): Connect to the supply grounding conductor.

Ensure all connections are secure and properly insulated.

Step 4: Secure Fixture Backplate

Carefully position the wiring inside the junction box. Align the fixture backplate (5) with the mounting bracket (1) and secure it using the provided fastening hardware. Ensure the backplate is flush against the wall and that no wires are pinched.

Step 5: Install Glass Shade

Position each glass shade (6) over its corresponding lamp holder (4). Secure each shade using the retaining ring (7). Hand-tighten until the shades are firmly seated. Do not overtighten, as excessive pressure may damage the glass.

Step 6: Install Light Bulb

Install a compatible light bulb (8) into each lamp holder (4). Ensure the bulbs do not exceed the fixture's maximum rated wattage.

Step 7: Restore Power and Test

Restore power at the circuit breaker. Turn ON the fixture and verify that all three lamps operate properly.

