

WARNING

PLEASE READ ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION

- To prevent personal injury or product damage, only licensed electricians should install.
- To avoid electric shock or component damage, disconnect power before attempting installation or servicing.
- This product must be installed in accordance with the national electric code (NEC) and all applicable federal, state and local electric codes and safety standards.
- Disconnect product and allow cooling prior to servicing.
- Any alteration or modification of this product is expressly forbidden as it may cause serious personal injury, death, property damage and/or product malfunction.
- To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects.
- This device is not intended for use with emergency exits.
- **CAUTION:** Connect fixture to a 120 Volt, 60Hz power source only. Any other connection void the warranty.
- Suitable for damp locations.

LIST OF RECOMMENDED DIMMERS

LUTRON: TGCL-153P, MACL-153M, CTCL-153P, PD-6WCL

LEVITON: IPL06-10Z, 6672-1LW, 6674-POW, DLS06-1LZ

Installation

1. Turn off power at the circuit breaker or electrical box before starting installation.
2. Remove the metal ring and plastic shade from the ceiling pan by unscrewing the cap nuts.
3. Attach the two mounting screws to the junction box, and screw them in 2 to 3 turns,
4. Pull out the source wires from the junction box. Connect the wires using wire connectors as follows:
 - Connect the wire (black insulation) from the fixture to the black wire from the power source.
 - Connect the wire (white insulation) from the fixture to the white wire from the power source.
 - Attach the fixture ground wire (bare wire) to the outlet box, Then connect it to the house ground wire with the wire connector.
 - Carefully put the wire back in to the junction box.
5. Attach the ceiling pan to the junction box by inserting two mounting screws in to the key holes, and rotate the ceiling pan until it is locked in place, then secure the mounting screws tightly.
6. Select the color temperature you need by setting the toggle switch to the corresponding color temperature.
7. Place the plastic shade into the metal ring, attach them up to the ceiling pan by inserting the threaded studs, then secure them with cap nuts.

