

Date:	
Project Name:	
SKU #:	

HELIX™ S
Flush Mounted Square Fixture



APPLICATIONS

Residential, Commercial, Multi-Family Complex, Hospitality

FEATURES

Construction

- Die-cast Aluminum Base
- Spun Aluminum Body

Optical

- Beam Angles:
 - 15°
 - 30°
 - 45°

Electrical & Technical

- Input Voltage: 100-277V
- Input Frequency: 50/60Hz
- Projected Life: L70 > 50,000 hrs
- PF: >0.9
- CRI: >90
- THD: <20%
- CCT: 2700K, 3000K, 4000K, 5000K
- Operating Temp.: -40°F ~ 122°F
- Dry Location

Installation/Mounting

- Pendant Mount:
 - 3.3' Cable [Standard]
 - 3.3' Stem [Standard] [Custom Length*]
- Surface Mount

Controls

- Triac Dimming [Option]
- 0-10 Dimming [Option]


Warranty

- 5 Year Warranty
See warranty documentation for more information.

Lumen Output

- 15W: 1,200lm
- 20W: 1,600lm
- 30W: 2,400lm

HOUSING FINISHES



REFLECTOR FINISHES




ORDERING INFORMATION **EXAMPLE: HXS-0305-15-30-15-D-BK-WH-CM**


Series	Size	Wattage	CCT	Beam Angle	Dimming	Finish	Reflector	Mounting Option
HXS	0305 - L: 3" x W: 3" x H: 5"	15 - 15W	27 - 2700K	15 - 15°	D - Triac Dimming D1 - 0-10V Dimming	BK - Black WH - White	BK - Black WH - White SV - Silver	CM - Cable Mount [3.3'] ST - Stem Mount [3.3'] SM - Surface Mount
	0306 - L: 3" x W: 3" x H: 6"	20 - 20W	30 - 3000K	30 - 30°				
	0406 - L: 4" x W: 4" x H: 6"	30 - 30W	35 - 3500K 40 - 4000K	45 - 45°				

DIMENSIONS

Pendant Mount



Surface Mount



LUMEN OUTPUT

SKU	Size [LxWxH] (in)	Wattage (W)	Delivered Lumens (lm)	Efficacy (lm/W)
HXS-0305-15-30-15-D-BK-WH-XX	3 x 3 x 5.5	15	1200	80
HXS-0306-20-30-15-D-BK-WH-XX	3.75 x 3.75 x 5.8	20	1600	70
HXS-0406-30-30-15-D-BK-WH-XX	4.5 x 4.5 x 6	30	2400	80