

	Eco AIR™ Backlit Panel	Thintek™ G2 Panel	Eco™ 110 Panel (S-F)	Eco™ 130 Panel (L-F)	Eco AIR™ LC Backlit Panel
					
	<i>Great Value</i>	<i>Best for Flush Mount</i>	<i>Slim Profile</i>	<i>Best Efficacy</i>	<i>Versatile</i>
ATTRIBUTES	<ul style="list-style-type: none"> • Slim Profile Backlit • Lightweight and Versatile • DLC Standard Listed 	<ul style="list-style-type: none"> • Integrated AC Edgelit • Ideal for Low-Ceiling Space • DLC Standard Listed 	<ul style="list-style-type: none"> • Slim Profile Edgelit • Visual Comfort Illumination • DLC Standard Listed 	<ul style="list-style-type: none"> • High Efficacy Edgelit • Premium Energy-Saving • DLC Premium Listed 	<ul style="list-style-type: none"> • Slim Profile Backlit • Field Adjustable Lumen Ouput • CCT Switchable
FEATURES	1'x4', 2'x2', 2'x4'	1'x4', 2'x2', 2'x4'	1'x4', 2'x2', 2'x4'	1'x4', 2'x2', 2'x4'	1'x4', 2'x2', 2'x4'
	5,250 lm (Max)	5,500 lm (Max)	7,150 lm (Max)	7,920 lm (Max)	6,875 lm (Max)
	4~9 lbs.	12~13 lbs.	8~16 lbs.	9-19 lbs.	5~10 lbs.
PERFORMANCE	50,000+ Hours (L70)	50,000+ Hours (L70)	50,000+ Hours (L70)	50,000+ Hours (L70)	50,000+ Hours (L70)
	105 LpW (Max)	110 LpW (Max)	110 LpW (Max)	125 LpW (Max)	125 LpW (Max)
	>80	>80 (+90 CRI Optional)	>80	>80 (+90 CRI Optional)	>80
	3500K, 4000K, 5000K	3500K, 4000K, 5000K	3500K, 4000K, 5000K	3500K, 4000K, 5000K	3500K, 4000K, 5000K
INTEGRATED COMPONENTS	Standard 0-10V Dimming				
	✓	✓	✓	✓	✓
	Emergency Backup Available				
	✓	✗	✓	✓	✓
	Driver				
	External 120-277 VAC	Integrated 120-277 VAC	External 120-277 VAC	External 120-277 VAC	External 120-277 VAC